



© Lalegno

Dimension plank

LENGTH	94-1/2" (2400 mm)
WIDTH	8-3/4" (220 mm)
TOTAL THICKNESS	5/8" (15 mm)

Dimension box

BOX LENGTH	96-1/2" (2450 mm)
BOX WIDTH	8-5/6" (225 mm)
BOX THICKNESS	3-2/3" (90 mm)
BOX WEIGHT	57 lb
LAGEN/PAK	6
SQFT/BOX	34.12 sqft

Dimension pallet

PALLET LENGTH	96-1/2" (2450 mm)
PALLET WIDTH	45-1/3" (1150 mm)
PALLET HEIGHT	34-2/3" (880 mm)
GEWICHT PALLET	2320 lb
BOX/PALLET	40
SQFT/PALLET	1364.86 sqft

FEATURES

Top layer

HOUTSOORT	Oak
LATIJSSE NAAM	Quercus Robur
SORTERING	CLASSIC
OPBOUW	3-layer
VELLING	Micro bevel 4 sides (0.5 mm)
OPPERVLAKTESTRUCTUUR	Brushed

Composition of the support

SUPPORT TYPE	Fir
BASE OF THE SUPPORT	Fir

Placement

SYSTEM	APPLICATIONS	VLOERVERWARMING
Tongue and groove	· Light household use · Moderate commercial use · Normal commercial use · Normal household use · Intensive commercial use	Yes
		HERSCHUURBAAR
		Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	CARB PH2	CARB PH2
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

