



Dimension plank

LENGTH	86 1/2" RL (2200 mm RL)
WIDTH	7" (180 mm)
TOTAL THICKNESS	9/16" (14 mm)

Dimension box

BOX LENGTH	87" (2210 mm)
BOX WIDTH	7 1/2" (190 mm)
BOX THICKNESS	3 2/6" (85 mm)
BOX WEIGHT	40 lb
LAGEN/PAK	6
SQFT/BOX	25.62 sqft

Dimension pallet

PALLET LENGTH	87 4/5" (2230 mm)
PALLET WIDTH	47 1/4" (1200 mm)
PALLET HEIGHT	43 2/3" (1100 mm)
GEWICHT PALLET	2414 lb
BOX/PALLET	60
SQFT/PALLET	1537.20 sqft

FEATURES

Top layer

HOUTSOORT	Oak
LATIJSSE NAAM	Quercus Robur
SORTERING	PRIME
OPBOUW	2-layer
VELLING	Micro bevel 4 sides (0.5 mm)
OPPERVLAKTESTRUCTUUR	Smooth

Composition of the support

SUPPORT TYPE	Engineered
BASE OF THE SUPPORT	Plywood
TOTALE DIKTE DRAGER	11 mm

Placement

SYSTEM	APPLICATIONS	VLOERVERWARMING
Tongue and groove	· Light household use · Moderate commercial use · Normal commercial use · Normal household use · Intensive commercial use	Yes
		HERSCHUURBAAR
		Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	CARB PH2	CARB PH2
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

